DVR-510

Smart DVR with 4Channel MJPEG



Features

- Concurrent 4-channel real-time digital video recorder
- Smart digital surveillance system with high quality live display
- Hardware video codec engine on board
- Plug & Play with easy installation
- User-friendly function control from push button on front panel
- Remote surveillance management by networking
- Connect to any TV, no monitor required
- Option for IDE HDD

Introduction

Advantech Smart DVR-510 is the most cost-effective compact standalone DVR. Support up to 4CH real-time displaying and 30fps in recording mode. It is easy to install with Plug and Play connection. The buttons on the front panel make it easy to use. The advanced networking function provides remote control and remote viewing on PC client viewer.

Specifications

| Item | | Description | Remarks | |
|----------------------------------|-----------|--|---|--|
| Video Input Format | | NTSC/PAL | | |
| Operating System | | None | | |
| Video Input Channel | | 4Ch Composite | | |
| Video Output Channel | | 2Ch Composite & 1Ch S-Video | | |
| Video Loop-Though | | 4Ch composite | | |
| Audio Input | | 1Ch RCA | | |
| Audio Output | | 1xRCA | | |
| Remote Control Interface | | PC Client through Lan or Internet | | |
| Built-in Buzzer | | Video Lost , HDD Failure | | |
| Display Frame | NTSC | 120fps | 4x30fps | |
| | PAL | 100fps | 4x25fps | |
| Recording Frame Rate (guad mode) | NTSC | Max.30fps(quad) | | |
| | PAL | Max.25fps(quad) | | |
| Recording Frame Rate (each mode) | NTSC | Max.7.5fps | | |
| | PAL | Max.6.25fps | | |
| Recording Mode | | Continuous, manual, event programmed | | |
| Resolution | Display | NTSC:720x480 PAL:720x576 | | |
| | Recording | NTSC: 640x224, 320x112 PAL: 640x272, 320x136 | | |
| Compression Format | | Modified MJPEG (12-20K bytes/frame) | Low: 12Kb/frame Normal:15Kb/frame High:20Kb/frame | |
| Search Mode | | Time, date, camera | | |
| System recovery | | Auto-recovery capability after re-power on | | |
| HDD | | One IDE HDD | | |
| Network Interface | | Ethernet 10/100 Tx RJ-45 | | |
| Dimension (W x H x D) | | 290 x 57 x 232 mm | | |
| Weight | | 2.2 kg | | |
| Power Consumption | | AC Input : 100-240 V ~ 1.8 A , 50-60 Hz DC Output : 12V , 4.2 A | | |
| Temperature | | Working : 5° C - 45° C | | |
| | | Non – Working -10° C - 60° C | | |

Digital Video System

Advanced Specification

| Main Feature Setup | Carnera select, Record select, Record mode, Record frame, Video Quality, Record schedule, HDD drive setup, Sensor setup, Networking setup, others setup | 2 | | |
|------------------------|---|-----------------------------|--|--|
| Camera Display Select | All off, All display, one channel display | Digital Video Recorder | | |
| Record Select | All off, All record, one channel record | | | |
| Record Mode | Each full screen , Quad screen | | | |
| Record Frame | 1, 2, 3, 4, 5, 7, 10, 15, 30 fps | | | |
| Video Quality | Normal, Low, High | Storage Server NAS | | |
| Record Schedule | 24-hour period, Recording (T), Sensor recording (S), Record off (-) | | | |
| H.D.D Setup | Overwrite, Size, Used %, Format | | | |
| Sensor Setup | Record time, Alarm out time , Sensor trigger mode | | | |
| Sensor Trigger Mode | Not installed, Normal open, Normal close, Motion detection +N-C, Motion detection + N-O | CCTV Color Camera | | |
| Remote Control feature | Live view, Record, Playback | | | |
| Function button | Menu, Recording, Stop, Fast forward, Fast reverse, Pause, Channel, | | | |
| | | Advantech Enterprise Server | | |



| Part Number | Description |
|--------------------|---|
| DVR-510 | Smart DVR with 4Channel MJPEG |
| Option | IDE HDD |
| Language Selection | English, Chinese (Traditional), Chinese (simplified), German,Spanish, Italian, Russian |

Packing List

| • | Power Cord | X 1 |
|---|---------------------------|-----|
| • | User's Manual | X 1 |
| • | CD for PC Client Software | X 1 |
| • | AC/DC Adaptor | X 1 |

