

# ADAM-5202 ADAM-5240 ADAM-5030

2-port AMONet Master Module  
4-axis Stepping/Pulse-type Servo  
Motor Control Module

2-slot SD Storage Module



## Specifications

### General

- **Certifications** CE
- **Power Consumption** 0.5 W (Max.)
- **Connectors** RJ-45
- **LED Indicators** Active, Error (Each Port)
- **Number of Rings** 2
- **Transmission Speed** 2.5, 5, 10 or 20 Mbps with automatic data flow control
- **Serial Interface** Half duplex RS-485 with transformer isolation
- **Cable Type** CAT5 UTP/STP Ethernet cable
- **Surge Protection** 10 kV
- **Communication** Max. 100 m (20 Mbps/32 slave modules) or 50 m (20 Mbps/64 slave modules) Distance
- **Communication Slave** 2 Rings with Max. 128 (1 Ring with 64 slaves) Module Number
- **Operating Temperature** 0 ~ 50° C (32 ~ 122° F)

Note: only for ADAM-5550 Series

## Ordering Information

- **ADAM-5202** 2-ring AMONet Master Module

## Specifications

### General

- **Certifications** CE
- **Power Consumption** 1.1 W (Max.)
- **Connectors** 100-pin SCSI-II female
- **Operating Temperature** 0 ~ 60° C (32 ~ 140° F)
- **Relative Humidity** 5 ~ 95 % RH non-condensing (refer to IEC 68-2-3)

### Motion

- **Number of Axis** 4 Axis
- **External Power input** DC +12 ~ 24 Vdc
- **Range** 2/3-axis Linear Interpolation/2-axis Circular Interpolation
- **Speed** ±2, 147, 483, 646 for each axis
- **Speed Curve** 1PPS ~ 4MPPS

### Continuous Interpolation

- **Speed** 1PPS ~ 2MPPS

### Drive Output Pulses

- **Range** 1PPS ~ 4MPPS
- **Pulse Output Type** Pulse /Direction (1-pulse, 1- direction type) Up/Down (2-pulse type) T/S-curve Acceleration/Deceleration
- **Speed Curve**

### Input Pulse for Encoder Interface

- **Encoder Pulse Input Type** Quadrature (A/B phase or Up/Down)
- **Counts per Encoder Cycle** X1, X2, X4 (A/B phase only)
- **Protection** 1000 Vdc isolation
- **Input Range** 5 V ~ 30 V

### External Signals Driving

- **Input Signal** nEXOP + and nEXOP
- **Max Input Frequency** 100 Hz
- **Protection** 1000 Vdc Photo coupler isolation

### External Deceleration/Instantaneous Stop Signal

- **Input Signal** nIN1 ~ 3
- **Max Input Frequency** 4 kHz
- **Protection** 1000 Vdc Photo coupler isolation

### Input Pulse for Servo Motor Drives

- **Input Signal** nALArm (servo alarm) nINPOS (position command completed)

### General Purpose Output Signal

- **Output Signal** nOUT4 ~ 7

### Emergency Stop

- **Input Signal** EMG – one emergency stop input for ADAM-5240
- **Protection** 1000 Vdc Photo coupler isolation and RC filtering

Note: only for ADAM-5550 Series

## Ordering Information

- **ADAM-5240** 4-axis Stepping/Pulse Servo Motor Control Module

## Specifications

### General

- **Certification** CE
- **Power Consumption** 0.5 W (Max.)
- **Storage Type** SD (Secure Digital Card)
- **Storage Number** 2
- **USB Type** USB Rev 2.0 (Compliant)
- **USB Number** 2
- **Operating Temperature** 0 ~ 60° C (32 ~ 140° F)
- **Max Storage** 1GB x 2
- **Format** FAT-16
- **Interface** PCI Bus

Note: only for ADAM-5550 Series

## Ordering Information

- **ADAM-5030** 2-slot SD Storage Module