



7923A Paired - Category 5e DataTuff® Twisted Pair Cable

 	<p>Metric Version For more information please call 1-800-Belden1</p> <p><u>See Put-ups and Colors</u></p> <p>Color Code Chart : No. 8 for DataTwist Cables (Modified Western Electric).pdf</p>
--	---

Description:

24 AWG Bonded-Pairs solid bare copper conductors, polyolefin insulation, industrial grade sunlight- and oil-resistant PVC jacket, rip cord. Sequential marking at two foot intervals.

SUITABLE APPLICATIONS:

Suitable Applications	Industrial Ethernet Cable, Harsh Environments, EtherNet/IP™ pair color, 350MHz Enhanced Category 5e, Gigabit Ethernet, 100BaseTX, 100BaseVG ANYLAN, 155ATM, 622ATM, NTSC/PAL Component or Composite Video, AES/EBU Digital Video, RS-422, CMX - Outdoor, RJ-45 Compatible
-----------------------	---

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Pairs	4
Total Number of Conductors	8
AWG	24
Stranding	Solid
Conductor Diameter	0.508 mm
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	PO - Polyolefin
Nom. Insulation Wall Thickness	0.229 mm
Insulation Diameter	0.889 mm

Pair Color Code Chart :

Number	Color	Number	Color
1	White/Blue Stripe & Blue	3	White/Green Stripe & Green
2	White/Orange Stripe & Orange	4	White/Brown Stripe & Brown

OUTER SHIELD:

Outer Shield Material	Unshielded
-----------------------	------------

OUTER JACKET:



7923A Paired - Category 5e DataTuff® Twisted Pair Cable

Outer Jacket Material	Industrial Grade PVC - Polyvinyl Chloride
Outer Jacket Ripcord	Yes

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	5.842 mm
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-40°C To +75°C
Storage Temperature Range	-40°C To +85°C
Installation Temperature Range	-25°C To +75°C
Bulk Cable Weight	37.205 Kg/Km
Max. Recommended Pulling Tension	177.928 N
Min. Bend Radius (Install)	6.35 mm

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR, CMX-Outdoor, UL444
CEC/C(UL) Specification	CMR
IEC Specification	11801 Category 5
EU RoHS Compliant (Y/N)	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
TIA/EIA Specification	568-B.2 Category 5e
Other Specification	NEMA WC-63.1 Category 5e, UL verified to Category 5e, Ethernet/IP™ Compliant

FLAME TEST:

UL Flame Test	UL1666 Riser
CSA Flame Test	FT4

SUITABILITY:

Suitability - Outdoor	Yes
Sunlight Resistance	Yes
Oil Resistance	Yes

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Mutual Capacitance @ 1 KHz	49.215 pF/m
Maximum Capacitance Unbalance (pF/100 m)	66 pF/100 m
Nominal Velocity of Propagation	70 %
Maximum Delay (ns/100 m)	510 ns/100 m
Maximum Delay Skew (ns/100m)	25 ns/100 m



7923A Paired - Category 5e DataTuff® Twisted Pair Cable

Maximum Conductor DC Resistance @ 20 Deg. C 9 Ohms/100 m

Maximum DCR Unbalance @ 20 Deg. C 3 %

Max. Operating Voltage - UL 300 V RMS

ELECTRICAL CHARACTERISTICS - PREMISE:

Premise Cable Electricals Table 1 :

Frequency (MHz)	Max. Attenuation (dB/100 m)	Min. NEXT (dB)	Min. PSNEXT (dB)	Min. ACR (dB)	Min. PSACR (dB)	Min. Return Loss (dB)	Min. Structural Return Loss (dB)
1	2	65.3	65.3	63.3	63.3	20	
4	4	56.3	56.3	52.3	52.3	23.6	
8	5.7	51.8	51.8	46.1	46.1	25.4	
10	6.4	50.3	50.3	43.9	43.9	26	
16	8.1	47.3	47.3	39.1	39.1	26	
20	9.2	45.8	45.8	35.2	35.2	26	
25	10.3	44.3	44.3	34.1	34.1	25.5	
31.25	11.6	42.9	42.9	31.3	31.3	25	
62.5	16.8	38.4	38.4	21.6	21.6	23.5	
100	21.7	35.3	35.3	17.1	17.1	22.5	
155	27.7	32.5	32.5	4.7	4.7	19	
200	32	30.8	30.8	3.0	3.0	19	
250	36.4	29.3	29.3	>0	>0	18	
300	40.5	28.2	28.2	>0	>0	18	
310	41.3	27.9	27.9			18	
350	44.3	27.2	27.2			17	

Premise Cable Electricals Table 2 :

Frequency (MHz)	Input (Unfitted) Impedance (Ohms)	Fitted Impedance (Ohms)	Min. ELFEXT (dB)	Min. PSELFEXT (dB)
1	100 ± 12	95-110	63.8	60.8
4	100 ± 12	95-110	51.7	48.7
8	100 ± 12	95-107	45.7	42.7
10	100 ± 12	95-107	43.8	40.8
16	100 ± 12	95-107	39.7	36.7
20	100 ± 12	95-107	37.7	34.7
25	100 ± 15	95-107	35.8	32.8
31.25	100 ± 15	95-107	33.9	30.9
62.5	100 ± 15	95-107	27.8	24.8
100	100 ± 15	95-107	23.8	20.8
155	100 ± 18	100 ± 10	19.9	16.9
200	100 ± 20	100 ± 10	17.7	14.7
250	100 ± 20	100 ± 10	15.8	12.8
300	100 ± 20	100 ± 10	14.2	11.2
310	100 ± 20	100 ± 10	13.9	10.9
350	100 ± 22	100 ± 10	12.9	9.9



7923A Paired - Category 5e DataTuff® Twisted Pair Cable

NOTES:

Notes	US Patent #'s 5, 606, 151; 5, 734, 126. EtherNet IP is a trademark of ControlNet International, Ltd. under license by Open DeviceNet Vendor Association, Inc. Operating temperatures are subject to length de-rating. Cable passes -40C Cold Bend per UL 1581.
-------	--

PUT-UPS AND COLORS:

Item	Description	Put-Up (M)	Ship Weight (kgs.)	Jacket Color	Notes
7923A 0101000	4 PR #24 PP PVC	304.8	12.712	BLACK	C
7923A 0102000	4 PR #24 PP PVC	609.6	24.516	BLACK	C

C = CRATE REEL PUT-UP.

Revision Number: 4 Revision Date: 09-07-2005

© 2005 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden CDT Electronics Division believes this product to be in compliance with the following environmental regulations: California Proposition 65 Consent Judgment For Wire & Cable Mfgs.(San Francisco Superior Court Nos. 312962 And 320342); EU RoHS (Directive 2002/95/EC, 27-Jan-2003);Material manufactured prior to the compliance date may still be in stock at Belden facilities and in our Distributor's inventory. EU ELV (Directive 2000/53/EC, 18-Sept-2000); EU WEEE (Directive 2002/96/EC, 27-Jan-2003); And EU BFR (Directive 2003/11/EC, 6-Feb-2003). The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information and belief at the date of its publication. The information provided in the Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.