



SHAFT END DETAIL

KEY DETAILS

DIMENSION TABLE (MODEL WITHOUT BRAKE)

MODEL	LL	LR	LS	LW	S	LV	U	TAPER	WK	W	T	RH	TP	LP	LE
ECMA-C□0804E7	112.3	30	24.5	20	14	—	—	—	5	5	5	11.0	—	300	300
ECMA-C□0804EC	112.3	30	24.5	20	14	—	—	—	5	5	5	11.0	—	3000	3000
ECMA-C□0804G7	112.3	30	24.5	20	14	—	—	—	5	5	5	11.0	—	300	300



MOTOR CONNECTOR (MODEL W/□ BRAKE)		
PIN No.	FUNCTION	COLOR
1	U PHASE	RED
2	V PHASE	WHT
3	W PHASE	BLK
4	GND	GRN/YEL



ENCODER CONNECTOR (PLUG TYPE)			
PIN No.	FUNCTION		COLOR
	2500ppr	20bit	
1	A	T+	BLK
2	B	BAT_5V	WHT
3	Z		ORG
4	$\overline{A}$	T-	BLK/RED
5	$\overline{B}$	BAT_GND	WHT/RED
6	$\overline{Z}$		ORG/RED
7	DC+5V	DC+5V	BRN
8	GND	GND	BLU
9	SHIELD	SHIELD	SHIELD



ENCODER CONNECTOR (D-SUB TYPE)		
PIN No.	FUNCTION	COLOR
1	$\overline{Z}$	ORG/RED
2	$\overline{B}$	WHT/RED
3	B	WHT
4	A	BLK
5	$\overline{A}$	BLK/RED
6	GND	BLU
7	GND	BLU
8	VCC	BRN
9	Z	ORG
—	SHIELD	SHIELD

REV.	ECN NO.
V1.0	

台達電子工業股份有限公司
DELTA ELECTRONICS, INC.

Drawn: | Design:

Date: | ECN No.:

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF DELTA ELECTRONICS, INC. AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SELL OF APPARATUSES OR DEVICES WITHOUT PERMISSION.

DIMENSIONAL TOLERANCES

	( )		( )		( )		( )		ANGLES
DECIMALS	<50	±0.1	<50	±0.15	<50	±0.2	<30°	±0.1°
X	±0.3	>50~100	±0.15	>50~100	±0.2	>50~100	±0.25	30°~60°	±0.3°
X.X	±0.2	>100~200	±0.2	>100~200	±0.25	>100~200	±0.3	60°~90°	±0.5°
X.XX	±0.1	200~	±0.2%	200~	±0.25%	200~	±0.3%		

Drawing Name: ECMA-C□0804□□

A3 SIZE | THIRD ANGLE PROJECTION | Part No.: | REV. V1.0

USED ON XXXXXX | UNIT mm | SCALE ------ | SHEET 1 OF 1

DF-MEA3H-3R00